



1188 James D. Hagood Highway
P.O. Box 1066
South Boston, VA 24592
info@southbostonspeedway.com



SECTION 5 – 2025 PURE STOCK RULES

Updates in red | Updated 10/24/2024

5-1 Competing Models:

- A. 1972 - Present four (4) Cylinder passenger cars.
 - 1. No pick-up trucks permitted.
 - 2. No four-wheel drives (4WD).
 - 3. No rotary engines.
 - 4. No turbo or super charge engines.
 - 5. No mid-engine cars.
 - 6. No convertibles.
 - 7. Automatic or manual transmission permitted.
 - 8. Only front or rear wheel drive cars are permitted.
- B. All parts must be readily available for make and model.

5-2 Safety

- A. Stock steering column only. Locking steering mechanism must be removed.
- B. All steering wheels must be magnetic and equipped with a quick release coupling. No more than one (1) inch aluminum steering wheel spacer permitted.
- C. Approved window net must be installed on the driver's side and must be released from the top, must meet NASCAR rulebook on installation.
- D. Five-point or more racing harness mandatory. No older than five (5) years.
- E. Approved racing type aluminum seats mandatory.
- F. No seat may be attached to the floorboard.
- G. Seats must have an approved type of frame. Must meet NASCAR rulebook.
- H. A working ABC three-pound chemical fire extinguisher is required, with a gauge that is visible to Track Officials. Must be solid mounted.
- I. Two-way working radios are mandatory. Spotter's are mandatory and must be in spotter's tower.

5-3 Engine

- A. Aftermarket parts must meet OEM specs. Maximum overbore .040 must maintain OEM piston styles. Only A/C compressor may be removed. No Cosworth engines. No aftermarket parts or ported or polishing parts permitted.
- B. Aftermarket radiators may be used. Must remain in stock location within the radiator support.
- C. Cold air intakes may be used.

5-4 Factory Horsepower with driver

- A. 149 horsepower or less – weight will be adjusted according to practice, qualifying and race times.
- B. 150 horsepower or more must weigh 2,600 lbs.: 45% right side and 55% left side
- C. Weight and horsepower must be displayed on the left fender.
- D. No modification of any stock parts not mentioned in the engine specifications to include vacuum lineage and air induction compartments.
- E. Twin-cam Nissan 240sx engine must have OEM style 16CC dished pistons.

5-5 Eight (8) Valve Engine Only – Carbureted

- A. Maximum overbore .060, must maintain OEM Style piston.
- B. Holley Street Carburetor Part No. 0-7448 allowed (No Modifications)
- C. Maximum 55% left side weight.

5-6 Ride Height

- A. Must be a minimum of 4.5 inches with driver in car.

5-7 Exhaust System

- A. Cars running stock exhaust manifolds can take 25 lbs. total off.
- B. Maximum three (3) inch exhaust pipe size.

5-8 Body

- A. Trunk and hood must have at least two (2) hood pins.
- B. The body must remain stock and must be made of steel. Fenders cannot be cut or flared for tire clearance. Wheel wells must remain stock and intact. Headlights and parking lenses must be removed, and openings filled completely with sheet metal. All bumpers must remain stock. Inner door panels can be removed. Fabricated dashboards are permitted but must remain full and in stock location.
- C. Hood may be a flat fiberglass LMSC hood

- D. All glass must be removed, including windshield. Lexan windshield and rear glass must be installed with two inside support straps, bolted (not riveted).
- E. Maximum rear spoiler size of five (5) inches tall and width of trunk. Spoiler must remain one height from left side to right side of car. All spoilers must be at rear of car.
- F. All components not listed must be factory OEM parts.

5-9 Frames

- A. Only stock firewall and floor pan in stock location permitted. Trunk area must remain stock. Tow Hook's must be installed on front horns, in front of radiator support by using a 3/8" dia. Steel chain or a 3/8-inch dia. rod (loop) and bolted or welded in place. Tow hooks must be installed in trunk area near the rear of car using same type hook as on the front of car.
- B. Solid or rubber bushings are allowed as long as mounting holes stay in the center location with no adjustments. No offset bushings are allowed. Must remain in stock location on rear cradle.

5-10 Roll Bars:

- A. A minimum six (6) point roll cage is required, and all roll cages must be acceptable to track officials. 1 3/4 inch OD; .095-inch thick. All cars must have a minimum of four (4) left side door bars and three (3) right side door bars. No straight door bars permitted.
- B. Rear hoop bar mandatory around fuel cell/gas tank in trunk area. It needs to be 1 3/4-inch OD; .095-inch thickness required.
- C. A reinforcement bar minimum 1 1/2 inches in diameter and with a minimum wall thickness of 0.083 inches magnetic steel tubing. Must extend below the rear frame section behind the fuel cell/fuel tank. This reinforcement bar must be attached to the rear frame rails on both left and right side. The reinforcement bar must be as wide as the rear frame rails and extend as low as the bottom of the fuel cell/fuel tank with two vertical uprights.

5-11 Fuel Tank

- A. Fuel cell optional. Maximum volume 8 gallons. Installed in trunk area and centered in frame or spare tire hole.
- B. No offsetting of fuel cell.
- C. Fuel injected cars may use stock gas tanks and must run less than one-half (1/2) capacity. Fuel line cannot run through Driver's compartment.
- D. No fuel additives are allowed.

5-12 Electrical System

- A. Battery must be mounted in driver compartment, enclosed in steel box with lid.
- B. All electrical switches must be operable and must be located within reach of the driver, but not in the left side door area, except the labeled on/off rotary-type master switch with "on" being in the

clockwise direction, which must be located at or on the front of the dash panel in the center. The on/off switch must be wired to the battery cable in a manner that would cut off all electrical power in the car. Cars without dashes may be replaced with a flat ignition system mounting plate in center of driver's compartment. Plate must be constructed of metal.

5-13 Brakes

- A. Brakes must remain stock. No brake bias adjusters are allowed.

5-14 Suspension

- A. Stock suspension parts permitted. Any adjustable control arms must be pre-approved by Track Officials. If not pre-approved, subject to disqualification. Stock springs must be equal in dimensions left to right plus or minus $\frac{1}{4}$ inch in height. No cutting or lightening of suspension parts permitted including springs. No racing shocks. Strut brackets cannot be altered in any way. Wheelbase must remain stock within $\frac{1}{2}$ inch.
- B. Upper strut caster camber plates may be used on front only and must be in stock location.
- C. Any car rear-ends allowed within the same make.
- D. No quick-change or nine (9) inch Ford rear-ends permitted.
- E. Any differential, open, welded, full spool, mini spool, locker, limited slip, or helical gear types allowed.
- F. Any gear ratio allowed
- G. Maximum rear steer of $\frac{1}{4}$ -inch.
- H. 1.5 degrees camber in left rear and right rear. Zero (0) tolerance on camber.
- I. Two (2) degrees maximum left front camber and maximum six (6) degrees in right front with driver in car. Zero (0) tolerance on camber.
- J. Adjustable FRONT TENSION RODS are authorized only for the Nissan 240's for safety but must be adjusted to stock length.
- K. All components not listed must be factory OEM parts.
- L. Maximum tread width of 62 $\frac{1}{2}$ inches front and rear.
- M. May run a Mustang two (2) manual rack and pinion or modify stock rack and pinion from power steering to manual. Cars running a manual rack must run a decal on the left fender and carry an additional 25 lbs. total weight.

5-15 Wheels

- A. Aftermarket steel wheels permitted with standard offset, all wheels must have same offset, maximum width seven (7) inches. Three (3) inch offset to allow for wheel clearance only.

5-16 Tires

- A. See Tire rules section.

5-17 Drive Train

- A. Clutch and transmission assembly must remain stock for make and model. Bell housing must have two (2) inch inspection hole. Clutch, fly wheel and pressure plate must weigh within 1 lb. of factory specifications. All gears must be in working order.

5-18 Claimer Rules

- A. There will be a \$50 track fee per item being claimed with a maximum of \$150 track fee. The driver must bring written items being claimed along with the cash for the claimed items before the last car has crossed scales at conclusion of the event. The driver must also finish one spot behind the car having items claimed.
- B. **Claimer items:**
 - 1. \$300.00 on computer.
 - 2. \$200.00 Claiming Rule per strut assembly. (Example shock and spring)
 - 3. \$600.00 Claiming Rule on transmission.

5-19 Protest Rules

- A. There will be a track fee per item being protested with a maximum of \$250 track fee.
The driver must bring written items being protested along with the cash for the protested items before the last car has crossed scales at conclusion of the event. The driver must also finish one spot behind the car being protested.
- C. The Protester must be willing to have his/her items inspected at the same time.
- D. See General Rules for full protest policies.
- E. **Protest Items:**
 - 1. External engine components – \$200. Speedway retains half for each item protested.
 - 2. Top internal engine components – \$350. Speedway retains half for each item protested.
 - 3. Bottom engine components – \$750. Speedway retains half for each item protested.
 - 4. Flywheel and clutch components – \$150. Speedway retains half for each item protested.
 - 5. Rear-end components – \$150. Speedway retains half for each item protested.

5-20 Other

- A. Any component not listed in rules is to remain stock.
- B. Track Officials retain the right to approve or disapprove of rules not listed above.
- C. At any time, Track Officials can modify rules for individual cars to equal the competition.

*OEM = Original Equipment Manufacturer

South Boston Speedway Track Officials reserve the right to issue bulletins to the rules to ensure fairness in competition.